

# AXIOM™ Coffee Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers

Automatic  
Decanter Coffee Brewers




**AXIOM-DV-3**  
(2 upper warmers,  
1 lower warmer - 2U, 1L)  
(Decanters sold separately)



## PRODUCT FEATURES

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Dual voltage adaptable. Can operate at 120V/15 amp or 120/208-240V/20 amp.
- Adjusts automatically to varying water pressure.
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front panel.
- Digital temperature control and accuracy.
- Ensures coffee brew quality with cold brew lock out capability.
- Electronic diagnostics and built in tank drain make service easier.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature control.
- Automatic warmer shut-off.
- Energy-saver mode reduces tank temperature during idle periods.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations

## AXIOM Coffee Brewers with Upper/Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
AXIOM-15-3	38700.0000	18.9"H x 8.5"W x 17.7"D (49cm H x 21.6cm W x 44.9cm D)	30 lbs. (13.6 kg)	120	15	1800	4.2 gal/hr 15.9 L/hr	Plastic	Yes	 
AXIOM-35-3	38700.0001			120/240	17.5	3850	7.5 gal/hr 28.4 L/hr		No	
AXIOM-DV-3	38700.0008			120	15	1800	4.2 gal/hr 15.9 L/hr		Yes	
AXIOMP-3-DV (with pourover feature)	38700.0023	21"H x 8"W x 17.7"D (53.3cm H x 20.3cm W x 44.9cm D)	32 lbs. (14.5 kg)	120/240	17.5	3850	7.5 gal/hr 28.4 L/hr			

# Decanter Coffee Brewers



**CWTF**  
(2 upper warmers,  
1 lower warmer - 2U, 1L)  
(Decanters sold separately)




**CWTF**  
(1 upper warmer,  
1 lower warmer - 1U, 1L)  
(Decanters sold separately)



## PRODUCT FEATURES

- All stainless steel construction.
- CWTF models feature hot water faucet and pourover backup on all models.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters – Product No. 20115.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations (CWTF only)

## 12 Cup Coffee Brewers with Upper/Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CWTF15	12950.0211 (1U, 1L)	18.9"H x 8.5"W x 17.8"D (48cm H x 21.6cm W x 45.2cm D)	32.5 lbs. (14.5 kg)	120	13	1570	3.9 gal/hr 14.6 L/hr	Plastic	Yes	 
CWT15 (no faucet)	12950.0356 (2U, 1L)		30 lbs. (13.6 kg)		13.9	1670				
CWT20 (no faucet)	12950.0291 (2U, 1L)				17.9	2150	7.5 gal/hr 28.4 L/hr	No		
CWT35 (no faucet)	12950.0292 (2U, 1L)			120/208-240	17.1	3850			7.5 gal/hr 28.4 L/hr	
CWTF15-3	12950.0213 (2U, 1L)			33 lbs. (14.97 kg)	120	13.9	1670	3.9 gal/hr 14.6 L/hr		
	12950.0217 (2U, 1L)		34 lbs. (15.4 kg)	17.9					2150	
CWTF20-3	12950.0283 (2U, 1L)		31 lbs. (14.1 kg)		120/240	17.1	3850	7.5 gal/hr 28.4 L/hr		
CWTF35-3	12950.0253 (2U, 1L)		30 lbs. (13.6 kg)	120					13.9	
	12950.0261 (2U, 1L)		32 lbs. (14.5 kg)		120/208	13.9	2640	6.7 gal/hr 25.3 L/hr		
CWTF-DV	12950.0410 (2U, 1L)		35 lbs. (15.9 kg)	120					13.9	
		120/240		15.6	3400	7.5 gal/hr 28.4 L/hr				

# AXIOM™ Coffee Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers

Automatic  
Decanter Coffee Brewers





**AXIOM-15-3**  
(3 lower warmer - 3L)  
(Decanters sold separately)

## PRODUCT FEATURES

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Adjusts automatically to varying water pressure.
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front panel.
- Electronic diagnostics and built in tank drain make service easier.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion, pulse brew and digital temperature control.
- Automatic warmer shut-off.
- Energy-saver mode reduces tank temperature during idle periods.
- Hot water faucet.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

## AXIOM Coffee Brewers with Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
AXIOM-15-3	38700.0002	16.8"H x 16.5"W x 17.7"D (42.7cm H x 41.9cm W x 45cm D)	31 lbs. (14.1 kg)	120	15	1800	4.2 gal/hr 15.9 L/hr	Plastic	Yes	 
AXIOM-35-3	38700.0003			120/240	17.5	3850	7.5 gal/hr 28.4 L/hr		No	
AXIOM-DV-3	38700.0009	18.9"H x 8.5"W x 17.7"D (48cm H x 21.6cm W x 44.9cm D)	32 lbs. (14.5 kg)	120	15	1800	4.2 gal/hr 15.9 L/hr		Yes	
				120/208	15.5	2980	7.5 gal/hr 28.4 L/hr			
				120/240	17.5	3850				

# Decanter Coffee Brewers




**CWTF**  
(3 lower warmers - 3L)  
(Decanters sold separately)



## PRODUCT FEATURES

- All stainless steel construction.
- CWTF models feature pourover backup on all models.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters – Product No. 20115.0000.
- Low profile for under cabinet placement.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations (CWTF only)

## 12 Cup Coffee Brewers with Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CWTF15	12950.0293 (1L)	16.8"H x 8.5"W x 17.8"D (42.7cm H x 21.6cm W x 45.2cm D)	27 lbs. (12.2 kg)	120	12.3	1470	3.9 gal/hr 14.6 L/hr	Plastic	Yes	 
CWTF15	12950.0298 (3L)		35 lbs. (15.9 kg)		13.9	1670				
CWTF35	12950.0381 (3L)	39 lbs. (17.7 kg)	120/208-240	17.1	3850	7.5 gal/hr 28.4 L/hr	Stainless	No		
CWT15-3 (no faucet)	12950.0112 (3L)	17"H x 16.5"W x 17.7"D (43.2cm H x 41.9cm W x 45.2cm D)	32 lbs. (14.5 kg)	120	13.9	1670	3.9 gal/hr 14.6 L/hr	Plastic	Yes	
CWTF15-3	12950.0212 (3L)		35 lbs. (15.9 kg)							
	12950.0216 (3L)		36 lbs. (16.4 kg)							
CWTF20-3	12950.0232 (3L)		35 lbs. (15.9 kg)						17.9	
CWTF35-3	12950.0252 (3L)		120/240	16	3850	7.5 gal/hr 28.4 L/hr				
CWTF-DV	12950.0409 (3L)		39 lbs. (17.7 kg)	120	15	1800	3.9 gal/hr 14.6 L/hr	Stainless	No	
				120/208	15.5	2980	6.7 gal/hr 25.3 L/hr			
				120/240	17.5	3850	7.5 gal/hr 28.4 L/hr			

# Decanter and AXIOM™ Coffee Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers



**CWTF Twin**  
(0/6 Twin)  
(Decanters sold separately)



**CWTF Twin**  
(2/2 Twin)  
(Decanters sold separately)



**AXIOM Twin**  
(0/6 Twin)  
(Decanters sold separately)



**AXIOM Twin**  
(4/2 Twin)  
(Decanters sold separately)


## CWTF FEATURES

- Medium volume, twin brew head systems.
- Four or six individually controlled warming stations.
- All stainless steel construction.
- Pourover feature on both sides.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters - Product No. 20115.0000.



## AXIOM FEATURES

- Twin brew head systems.
- Brews 15 gallons (56.8 litres) of perfect coffee per hour.
- Six individually controlled warmers.
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front panel.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Electronic diagnostics and built-in tank drain make service easier.
- Coffee extraction controlled with programmable pre-infusion and pulse brew features.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations (CWTF only)

## 12 Cup Coffee Brewers with 4 or 6 Warmers

Model	Product #	Size		Electrical			Legs	Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CWTF 2/2 Twin	23400.0001	19.3"H x 16.5"W x 19.8"D (49cm H x 41.9cm W x 50.3cm D)	56 lbs. (25.4 kg)	120/240	27.7	6650	n/a	15 gal/hr 56.8 L/hr	No	 
CWTF 4/2 Twin	23400.0011				28.5	6850				
CWTF 0/6 Twin	23400.0020	20.54" H x 30.75" W x 20.64" D (52.17cm H x 78.11cm W x 50.43cm D)	74 lbs. (33.6 kg)		28.5	6850	4" satin nickel legs			
AXIOM 4/2 Twin	38700.0014	19.1"H x 16.4"W x 17.7"D (48.5cm H x 41.7cm W x 44.9cm D)	61 lbs. (27.7 kg)	120/ 208-240	27.9	6700	n/a			
AXIOM 0/6 Twin	38700.0015	20.5" H x 30.3" W x 17.7" D (52.1cm H x 77cm W x 45cm D)	74 lbs. (33.6 kg)				4" black legs			

# Automatic Brewers



**OL**

(Decanters sold separately)

**OT**

(Decanters sold separately)

## OT/OL FEATURES

- Two separately controlled warmers.
- Designed to function well in low or uneven water pressure situation. (OL models)
- All stainless steel construction.
- OL models can also be operated as a pourover unit.
- Faucet kit available.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters - Product No. 20115.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*





**VLPF**

(Decanters sold separately)

## VLPF FEATURES

- Internal stainless steel components.
- Two individually controlled warmers.
- SplashGard® deflects hot liquids away from the hand.
- Use BUNN paper filters - Product No. 20115.0000.

## Automatic Brewer with 2 Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts			
OL 20	20820.0001	23.5" H x 12" W x 18.5" D (59.7cm H x 30.5cm W x 47cm D)	34 lbs. (15.5 kg)	120	17	2050	6 gal/hr 22.7 L/hr	No	 
OL 35	20820.0002			120/240	15.6	3750	7.5 gal/hr 28.4 L/hr		
OT 15	20830.0000	22.4" H x 12" W x 18.3" D (56.9cm H x 30.5cm W x 46.5cm D)	32.7 lbs. (14.8 kg)	120	13	1570	4.2 gal/hr 15.7 L/hr	Yes	
OT 20	20830.0001				17.4	2090	5.3 gal/hr 19.9 L/hr	No	
VLPF	07400.0005	17.4" H x 23.5" W x 13.1" D (44.2cm H x 59.7cm W x 33.3cm D)	26.3 lbs. (11.9 kg)	120	13.3	1600	3.9 gal/hr 14.6 L/hr	Yes	

# Decanter Coffee Brewers




**CRTF**  
(Decanters sold separately)

**PRODUCT FEATURES**

- Five separately controlled warmers.
- All stainless steel construction.
- Models available with faucet. Faucet kits available for existing models.
- SplashGard® funnel deflects hot liquids away from the hand.
- Designed to function well in low water pressure situations, the RL model can also be operated as a pourover unit.
- CRTF model has hot water faucet and pourover feature.
- Use BUNN paper filters - Product No. 20115.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*



 International electrical configurations (RL only)



**RL**  
(Decanters sold separately)



**RT**  
(Decanters sold separately)

12 Cup Coffee Brewer with 5 Warmers										
Model	Product #	Size		Electrical			Funnel Type	Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CRTF5-35	13250.0023	17.1" H x 24 5" W x 18.2" D (43.4cm H x 62.2cm W x 46.2cm D)	50.2 lbs. (22.8 kg)	120/240	16.9	4050	Plastic	7.5 gal/hr 28.4 L/hr	No	 
CRTF5-35	13250.0025		48 lbs. (21.8 kg)							
RT	20835.0000	21.2" H x 24" W x 18.5" D (53.8cm H x 61cm W x 47cm D)	42 lbs. (19.1 kg)							
RTF (w/faucet)	20835 0004	46 lbs. (20.9 kg)								
RL	20825 0000	23.5" H x 24" W x 18.5" D (59.7cm H x 61cm W x 47cm D)	44 lbs. (20.0 kg)							

# Coffee Urns




SRU

### 3 GALLON URN FEATURES

- Automatic drip brewing of delicious coffee every time.
- Large water tank holds over 10 gallons.
- Draw off hot water during brewing cycle without affecting delivery of coffee.
- All stainless steel construction.
- Brews full or half batches.
- Top mounted components ease service.
- Use BUNN paper filters - Product No. 20109.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations

### TWIN 3 GALLON FEATURES

- Unique design assures extremely low evaporation loss to maintain the brew at its flavorful peak.
- Large water tank holds over 20 gallons.
- Draw off hot water during brewing cycle without affecting coffee quality.
- Half-batch option.
- Top mounted components ease service.
- All stainless steel construction.
- Use BUNN paper filters - Product No. 20109.0000.



*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations



U3

## Coffee Urns

Model	Product #	Size		Electrical			Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts			
SRU	06325.0001	33.5" H x 14" W x 24.6" D (85.1cm H x 35.6cm W x 62.5cm D)	73 lbs. (33.1 kg)	120/208	19.4	4025	11.4 gal/hr.	No	
	75 lbs. (34.0 kg)		120/240	16.8					
U3 (Single Serve)	20500.0000	32.4" H x 34.5" W x 21" D (82.3cm H x 87.6cm W x 53.3cm D)	103 lbs. (46.8 kg)	120/208	28	5825	16.3 gal/hr.	No	
	20500.0001		120/240	6725		18.8 gal/hr.			