

Low Profile Liquid Coffee Ambient Dispenser

ITEM# _____

PROJECT _____

DATE _____

Features

Low Profile Ambient Dispenser

- Attractive appearance with shorter profile.
- Dispense over 120 (5 oz.) cups per hour.
- Accommodates two .5 gallon bag-in-box (BIB).
- Serves two coffee products and hot water.
- Refill LED lights alert the operator when more concentrate is needed.
- Rinse LED lights alert the operator cleaning is needed.
- Set up for continuous dispense (by the cup) for self-serve applications or portion-control to fill cups or carafes.



Model LCA-2 LP

Dimensions: 23.2" H x 15.78" W x 20.9" D
(58.9cm H x 40.1cm W x 53cm D)


For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQHP-10L
Product No. : 39000.0001
Use with 1.8 oz/sec. flow rate.



1/8" Replacement tube kits
Product No. : 37942.1000



Adapter/Tube Package
Scholle 1910
Product No.: 38800.0200

Adapter/Tube Package
QCDII
Product No.: 38800.0201

Adapter/Tube Package
Scholle Q/C
Product No.: 38800.0202

Adapter/Tube Package
Rapak
Product No.: 38800.0203

50ml Graduated Cylinder Kit
Product No. : 34843.1000
For use in calibration of pumps.



Model

LCA-2, LP

Agency Listing




Dimensions & Specifications

Model	Product Number	Dispense Rate 1.7 oz.	Connector Type	Volts	Amps	Heater Watts	Total Watts	Capacity*	Cubic Measure	Shipping Weight	Cord Attached
Product Ratios											
LCA-2, LP	38800.0000	25:1 - 100:1	Scholle 1910LX	120	12	1425	1440	120 cups/hr.	10.9 ft ³	65 lbs.	Yes
LCA-2, LP	38800.0001	25:1 - 100:1	QCDII	120	12	1425	1440	120 cups/hr.	10.9 ft ³	65 lbs.	Yes
LCA-2, LP	38800.0002	25:1 - 100:1	Scholle Q/C	120	12	1425	1440	120 cups/hr.	10.9 ft ³	65 lbs.	Yes
LCA-2, LP	38800.0003	25:1 - 100:1	Rapak	120	12	1425	1440	120 cups/hr.	10.9 ft ³	65 lbs.	Yes

*Capacity measured with a 5 oz. cup.

Electrical: 120V model requires 2-wires plus ground service rated 120V, single phase, 60 hz.

Plumbing: 20-90 psi (138-621 kPa) from a 1/4" (6.35 mm) or larger supply line. Unit requires a 1 gpm line flow capacity. A shut-off valve should be installed in the line before the unit. Install a regulator in line when pressure is greater than 90 psi to reduce pressure to 50 psi. Supplied with 1/4" (6.35 mm) male flare fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches.

12/08 © Bunn-O-Matic Corporation