

## Low Profile Liquid Coffee Chilled Dispenser

ITEM#

PROJECT

DATE

### Features

#### Low Profile Chilled Dispenser

- Attractive appearance with shorter profile.
- Dispense over 120 (5 oz.) cups per hour.
- Chilled product cabinet utilizes thermoelectrics for optimal performance.
- Accommodates two .5 gallon bag-in-box sized approximately 7.5"H x 5.25"W x 4"D.
- Internal product cabinet is approximately 8.5"H x 11.5"W x 5.5"D.
- Serves two coffee products and hot water.
- Refill LED lights alert the operator when more concentrate is needed.
- Rinse LED lights alert the operator cleaning is needed.
- Set up for continuous dispense (by the cup) for self-serve applications or portion-control to fill cups or carafes.



#### Model LCC-2 LP

Dimensions: 23.2" H x 15.78" W x 20.9" D  
(58.9cm H x 40.1cm W x 53cm D)

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

### Related Products

**Easy Clear® EQHP-10L**  
Product No. : 39000.0001  
Use with 1.8 oz/sec. flow rate.



**1/8" Replacement Tube Kits**  
Product No. : 37942.1000



**Drip Tray Drain Kit**  
Product No.: 37309.0000

**50ml Graduated Cylinder Kit**  
Product No. : 34843.1000  
For use in calibration of pumps.



#### Model

LCC-2, LP

#### Agency Listing



Patents Apply

12/08

A6.5


## Dimensions & Specifications

Model	Product Number	Dispense Rate 1.7 oz.	Connector Type	Volts	Amps	Heater Watts	Total Watts	Capacity*	Cubic Measure	Shipping Weight	Cord Attached
<b>Product Ratios</b>											
LCC-2, LP	38800.0004	25:1 - 100:1	Scholle 1910LX	120	12	1425	1440	120 cups/hr.	10.9 ft <sup>3</sup>	65 lbs.	Yes
LCC-2, LP	38800.0005	25:1 - 100:1	QCDII	120	12	1425	1440	120 cups/hr.	10.9 ft <sup>3</sup>	65 lbs.	Yes
LCC-2, LP	38800.0006	25:1 - 100:1	Scholle Q/C	120	12	1425	1440	120 cups/hr.	10.9 ft <sup>3</sup>	65 lbs.	Yes
LCC-2, LP	38800.0007	25:1 - 100:1	Rapak	120	12	1425	1440	120 cups/hr.	10.9 ft <sup>3</sup>	65 lbs.	Yes

\*Capacity measured with a 5 oz. cup.

Electrical: 120V model requires 2-wires plus ground service rated 120V, single phase, 60 hz.

Plumbing: 20-90 psi (138-621 kPa) from a 1/4" or larger supply line. Unit requires a 1 gpm line flow capacity. A shut-off valve should be installed in the line before the unit. Install a regulator in line when pressure is greater than 90 psi to reduce pressure to 50 psi. Supplied with 1/4" male flare fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches.

12/08 © Bunn-O-Matic Corporation